

EXISTING GRADE

EXISTING MANHOLE CASTING AND LID

EXISTING MANHOLE

CORE DRILL EXISTING CONCRETE MANHOLE AND INSTALL WATERSTOP RING OR BOOT

PROPOSED PVC SANITARY SEWER

SEE PIPE BEDDING REQUIREMENTS

BOTTOM OF TRENCH

NOTES:

1. REMOVE EXISTING INTERIOR BENCH AND RE-POUR BENCHES AND CHANNELS.
2. THE E.W.S.U. WILL VERIFY THE CONDITION OF THE PRECAST BASE AFTER REMOVAL OF THE INTERIOR BENCH TO DETERMINE IF STRUCTURAL INTEGRITY HAS BEEN COMPROMISED DURING REMOVAL. IF REMOVAL IS IMPRACTICAL OR UNSUCCESSFUL, THE ENTIRE BASE SECTION SHALL BE REPLACED.

EXISTING BENCH

EXISTING SANITARY SEWER PIPE

File: F:\ENGINEER\AUTOCAD\Standards\Drawings\Sewer\WW-10 New Pipe Connection to Existing MH.dwg



NEW PIPE CONNECTION TO EXISTING MANHOLE

Approved: 11/10/15

Adopted: 11/10/15

Figure

Approved By: Michael D. Labitzke, P.E.

Scale: N.T.S.

WW-10