


NOTES:

- ① From the Face of Curb to 2 feet past the Face of Curb, the Sign will be a minimum of 14 feet high.
- ② From 2 feet past the Face of Curb to the back of the Sidewalk, or a minimum of 5 feet from the Face of Curb where no Sidewalks exist, the Sign will be a minimum of 10 feet high.
- ③ From back of Sidewalk to a distance of 10' from the Face of Curb, the Sign will be a minimum of 6 feet high.
- ④ From 10 feet past the Face of Curb to the Right-of-Way Line, the Sign height can vary.
- ⑤ No Sign supporting system will be allowed within the limits of Notes ① & ②.
- ⑥ Sign supporting systems in the limits of Note ③ will be determined on an individual Sign basis.
- ⑦ No part of the Sign will be allowed to hang over into the Street.

▨ Indicates where sign is permitted.

Sign Encroachment Standards (For Curbed Street)

Rev Date 3/25/98



NOTES:

- ① From the Edge of Pavement to 10 feet past the Edge of Pavement, the Sign will be a minimum of 14 feet high.
- ② From 10 feet past the Edge of Pavement to the Right-of-Way Line, the Sign height and supporting systems will be determined on an individual Sign basis.
- ③ No Sign supporting system will be allowed within the limits of Note ①.
- ④ No part of the Sign will be allowed to hang over into the Street.

▨ Indicates where sign is permitted.

Sign Encroachment Standards (For Uncurbed Street)

Rev Date 3/25/98